

# DCE-S 10/12 Plus

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238154

**Compact DCE-S Plus instantaneous water heater – For easy showering pleasure.**

With its high efficiency and output, the DCE-S Plus offers a reliable and constant supply of hot water for several smaller draw-off points (hand washbasins) or one larger one (shower).

**As efficient as it is compact.**

The rotary selector quickly enables accurate temperature delivery between 20 and 60 °C. The temperature can be selected variably, either in °C or °F. The rotary selector makes operation extremely easy.



## The main features

Electronically controlled compact instantaneous water heater with 3i technology

Very good energy efficiency thanks to electronic output control

Precise temperature selection from 20 °C to 60 °C

Permanently selectable temperature limit can be set to 43 °C, 50 °C or 55 °C

Suitable for showers

Good price/performance ratio



Type	DCE-S 6/8 Plus + 2 x WSH 20	DCE-S 10/12 Plus + 2 x WSH 20	DCE-S 6/8 Plus
Part no.	203849	203848	238153
Rated output			6,0/8,0 kW
Height			372 mm
Width			217 mm
Depth			109 mm
<b>Technical data</b>			
Rated voltage 1			220 V
Rated output 1			6,0/8,0 kW
Rated current 1			27,3/36,4 A
Fuse 1			30/40 A
Frequency 1			50/60 Hz
Rated voltage 2			230 V
Rated output 2			6,6/8,7 kW
Rated current 2			28,5/38,0 A
Fuse 2			30/40 A
Frequency 2			50/60 Hz
Rated voltage 3			240 V
Rated output 3			7,2/9,6 kW
Rated current 3			30,0/40,0 A
Fuse 3			30/40 A
Frequency 3			50/60 Hz
Phases			1/N/PE
Temperature adjustment			20-60 °C

Specific resistance $\rho_{15} \geq$	1100 $\Omega$ cm
Specific conductivity $\sigma_{15} \leq$	910 $\mu\text{S}/\text{cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,5 kg



Type	DCE-S 10/12 Plus
Part no.	238154
Rated output	10,0/12,0 kW
Height	372 mm
Width	217 mm
Depth	109 mm

## Technical data

Rated voltage 1	220 V
Rated output 1	10,0/12,0 kW
Rated current 1	45,5/54,5 A
Fuse 1	50/60 A
Frequency 1	50/60 Hz
Rated voltage 2	230 V
Rated output 2	11,0/13,1 kW
Rated current 2	47,8/57,0 A
Fuse 2	50/60 A
Frequency 2	50/60 Hz
Rated voltage 3	240 V
Rated output 3	12,0/14,3 kW
Rated current 3	50,0/59,5 A
Fuse 3	50/60 A
Frequency 3	50/60 Hz
Phases	1/N/PE
Temperature adjustment	20-60 °C
Specific resistance $\rho_{15} \geq$	1100 $\Omega$ cm

Specific conductivity $\sigma_{15} \leq$	910 $\mu\text{S}/\text{cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP25
Weight	2,5 kg

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.