

SHZ 30 S (GB)

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 232783

The main features

Universal flanged immersion heater for dual circuit operation, optional single circuit operation/manual rapid heat-up operation

Infinitely variable temperature selection from 35 °C to 70 °C

Suitable safety valve included in standard delivery

Electronic heat content indication via LED in the user interface

Signal anode with indicator lamp in the user interface; can be replaced without removing the flange (50 - 150 l)

High-grade thermal insulation with the lowest heat losses

Maintenance free impressed current anode

Radiator connections through complete flanged plug

Drain valve with G 3/4 hose connection

Can also be installed with plastic pipework systems





Type	SHZ 30 S (GB)	SHZ 50 S (GB)	SHZ 100 S (GB)
Part no.	232783	232784	232786
Rated capacity	30 l	50 l	100 l
Width	410 mm	510 mm	510 mm
Height	846 mm	816 mm	1126 mm
Depth	420 mm	510 mm	510 mm

Technical data

Connected load with ~ 230 V	2-4 kW	2-4 kW	2-4 kW
Power supply	1/N/PE, 2/ N/PE, 3/N/PE	1/N/PE, 2/ N/PE, 3/N/PE	1/N/PE, 2/ N/PE, 3/N/PE
Rated voltage	230 V	230 V	230 V
Frequency	50 Hz	50 Hz	50 Hz
Standby power consumption/24 h	0,46 kWh	0,54 kWh	0,86 kWh
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Energy efficiency class	B	C	C
Weight	22,9 kg	27,6 kg	39,5 kg



Type	SHZ 150 S (GB)
Part no.	232788
Rated capacity	150 l
Width	510 mm
Height	1521 mm
Depth	510 mm

Technical data

Connected load with ~ 230 V	2-4 kW
Power supply	1/N/PE, 2/ N/PE, 3/N/PE
Rated voltage	230 V
Frequency	50 Hz
Standby power consumption/24 h	1,1 kWh
Colour	white
IP-Rating	IP24
Energy efficiency class	C
Weight	52 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.